




SUHNER FIBEROPTIC FSC-CMAX DUPLEX CONNECTOR

Features

- Nondestructive design for connectability and disconnectability
- One-piece design
- Spring loaded zirconia ceramic ferrule
- Special ferrule preform for short polishing time
- Channel markings A and B with separable links



Applications


- LAN, MAN
- Telecom
- CATV, sensor systems


Specifications

Fibre type	G50, 62.5/125µm
Insertion loss multimode	50% < 0.4dB; 98% < 0.8dB
Strain relief	crimped, 100N (conditioned by type of cable)
Operating temperature	-25° to +70°C (conditioned by type of cable)
Durability	min. 500 cycles
Assembly procedure	glue and polish
Connection	physical contact of ferrules
Lock mechanism	snap-on
Standard	according to IEC 874-14

Insertion loss multimode

Number of measurements





Ordering table

Connector

FSC-CMAX-B001-02

FSC-CMAX DUPLEX connector, multimode

Adapter

FSC-FSC-D200-02

FSC-CMAX DUPLEX adapter with 2-hole flange and phosphor-bronze sleeve

Crimpset black

009-BK-D001

for cable-Ø < 1.0mm

021-BK-D001

for cable-Ø 2.0 - 2.2mm

024-BK-D001

for cable-Ø 2.3 - 2.6mm

028-BK-D001

for cable-Ø 2.7 - 2.9mm

030-BK-D001

for cable-Ø 3.0 - 3.3mm

035-BK-D001

for cable-Ø 3.4 - 3.6mm

Waiver

While the information contained has been carefully compiled to the best of our present knowledge, it is not intended as representation or warranty of any kind on our part regarding the fitness of the products concerned for any particular use or purpose and neither shall any statement contained herein be construed as a recommendation to infringe any industrial property rights or as a license to use any such rights. The fitness of each product for any particular purpose must be checked beforehand with our specialists.



HUBER+SUHNER AG

Fiberoptic Division

9100 Herisau, Switzerland

Phone +41 (0)71 353 41 11

Fax +41 (0)71 353 46 47

www.hubersuhner.com